

Model		MRX-D3
RFID	Spec.	ISO/IEC 18000-63 (Former 18000-6C) / EPCglobal Class 1 Gen 2
	Radio frequency	840~960MHz
	Output	1~27dBm
	Reading distance	0~4m
	Polarization characteristics	Circularly Polarized Antenna (internal)
	Functions	Inventory/Read/Write/Lock/Kill
Power Source		USB Type-C Input: 5V/1A
Button		Trigger button, Dip switch
Interface	Communication interface	USB Type-C (for Android Phone)
	Power & communication interface	USB Type-C (for PC)
Appearance	Dimensions (W)x(D)x(H)	90 × 55 × 13mm
	Weight	Approx. 80g
	Material	PC+ABS
	Color	White
	LED indicator	[Operation Indicator] - Blue Power on: Slow flashing USB connection: Light on Reading RFID tags: Fast flashing
Environment	Operation temp.	-10 ~ 45 °C, 20 ~ 85%RH
	Storage temp.	-20 ~ 60 °C, 10 ~ 95%RH
	IP rate	IP54 compliant
	Anti-drop	(Six-sided, 4 edges, once each) 1.5m
Supporting OS		Windows, Android
Accessories		USB Type-A to USB Type-C data cable, Mounting frame